



Skid-Daddle®

Rubber Tire Mark Remover And Concentrated Floor Cleaner

P R O D U C T D A T A

DESCRIPTION

Skid-Daddle is a specially formulated cleaner designed to remove rubber tire marks from epoxy or other polymer floor coating systems without damaging the floor coating. **Skid-Daddle** is a blend of special cleaning agents, has a pale yellow color and fresh citrus fragrance.

USES

- Clean tire marks from multiple floor types such as surfaces coated with epoxy, novalac, urethane, methyl methacrylate, or vinyl ester polymer coatings
- General floor cleaner for plain concrete or polymer coated floors to remove tough grease, dirt, and oil

ADVANTAGES

- Cleans black rubber tire marks caused by a variety of wheeled devices such as forklifts, skid steers and rubber shoe soles without damaging polymer floor coatings
- Deep cleans dirt, oil, and grease from the pores and capillaries of plain concrete and multiple floor types
- Neutral pH
- Pleasant clean citrus fragrance
- Does not contain petroleum solvents

Packaging and Part Number

5 gal (183.9L) pails	F4.0241
55 gal (207.9L) drums	F4.0242

Use Dilution Rate With Clean Potable Water

1:1	Tire mark removal
10:1	General Floor Cleaning
20:1 to 50:1	Automatic Scrubbers Soil dependant

DIRECTIONS

As a spot cleaner on rubber tire marks:

Dilute **Skid-Daddle** 1:1 with water and spray or pour directly on the marks. Allow the solution to soften the tire mark for at least 15 minutes and then scrub the area. Rinse well with clean water.

As a general floor cleaner:

Dilute **Skid-Daddle** 10:1 with water. Rinse well with clean water.

In automatic scrubbers:

Dilute **Skid-Daddle** 20:1 to 50:1 with water depending on how heavily soiled the area is.

NOTE:

*Rinse well. Completely remove **Skid-Daddle** from the surface of the substrate.*

CLEANUP

Clean tools and equipment with clean water.

STORAGE

Store in tightly sealed containers in a cool dry area away from direct sunlight and sources of heat. Shelf life of properly stored material is two years from date of manufacture.

LIMITATIONS

- A test area is recommended. This is especially important if the exact chemistry of the floor sealer or coating is unknown. Apply **Skid-Daddle** diluted 1:1 with water to a 1ft²(0.3m²) area and scrub. If any deterioration of the coating or sealer is noticed or if the surface loses its sheen contact JTM Products for alternative recommendations.

PRECAUTIONS

- **Danger:** May be harmful if swallowed. Causes skin irritation. Causes serious eye damage. May cause respiratory irritation. Very Toxic to aquatic life.
- **Precautionary Statements:** Avoid breathing dust/fume/gas/mist/vapours/spray. Wash hands and skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

August 2021